

# The *Severe Service* Tranny Fluid

AMSOIL Universal Automatic Transmission Fluid offers outstanding performance in transmissions, power steering and hydraulic applications. It meets or exceeds the following performance specifications:

- GM Dexron II & III • Ford Mercon & Mercon V
- Chrysler ATF+ through ATF+4 • Allison C-3 & C-4
- Caterpillar TO-2 & TO-3 • Voith Commercial • Opel & GM Strasbourg

AMSOIL Universal Automatic Transmission Fluid resists oxidation and thermal degradation, provides low temperature and anti-wear protection, and offers extended drain intervals.



### HIGH TEMPERATURE FLUID LIFE TESTS

Tests Used Are GM'S THOT and Ford's ABOT Measuring TAN Increase

PETROLEUM ATF = 300 HOURS	RESISTS HIGH TEMPERATURE DEGRADATION THREE TIMES LONGER
AMSOIL SYNTHETIC ATF = 900 + HOURS	

### Synthetic Universal Automatic Transmission Fluid

Stock No.	Pkg/Size	Wt. Lbs. ea	Commission Credits, ea	US Retail, ea	Canada Retail, ea
ATF-QT	(1) quart bottle	2	4.50	7.55	11.75
ATF-01	(12) quart bottles	25	54.00	89.40	139.80
ATF-TP	(1) 2.5 gallon	19	45.05	71.75	110.50
ATF-05	(2) 2.5 gallons	38	90.10	141.50	219.00
ATF-30	30-gallon drum	234	345.00	659.00	1041.00
ATF-55	55-gallon drum	423	527.00	1126.00	1669.00

Call 1-800-777-7094 to order



**AMSOIL INC.**  
 SYNTHETIC LUBRICANTS  
 AMSOIL BUILDING  
 Superior, WI 54880-1527  
 (715) 392-7101  
 Internet: www.amsoil.com

**CHANGE SERVICE REQUESTED**  
 Published 12 times annually

PRSR STD  
 U.S. POSTAGE  
**PAID**  
 PERMIT NO.13  
 SUPERIOR, WI



JULY 2001  
 PRINTED IN USA

